

Utility Flatbed Trailers

MODEL	58R	610R	612R	8110R	8112R
LENGTH	8'	10'	12'	10'	12'
WIDTH	5'	6'	6'	81"	81"
RAIL HEIGHT	10"	10"	10"	10"	10"
FLOOR HEIGHT	20"	20"	20"	20"	20"
AXLE					
QUANTITY	ONE	ONE	ONE	ONE	ONE
CAPACITY	3500	3500	3500	3500	3500
TYPE	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
BEARING LUBE	EZ-LUBE	EZ-LUBE	EZ-LUBE	EZ-LUBE	EZ-LUBE
BRAKES*	OPTIONAL*	OPTIONAL*	OPTIONAL*	OPTIONAL*	OPTIONAL*
BREAKAWAY KIT*	OPTIONAL*	OPTIONAL*	OPTIONAL*	OPTIONAL*	OPTIONAL*
TIRE SIZE	ST205R15	ST205R15	ST205R15	ST205R15	ST205R15
TIRE LOAD RANGE	C	C	C	C	C
WHEEL BOLT PATTERN	5 - 4 1/2	5 - 4 1/2	5 - 4 1/2	5 - 4 1/2	5 - 4 1/2
HITCH BALL SIZE	2"	2"	2"	2"	2"
HITCH HEIGHT	19"	19"	19"	19"	19"
HITCH WEIGHT	95	105	110	110	115
CURB WEIGHT	950	1050	1100	1100	1150
GVWR	2990	2990	2990	2990	2990
PAYLOAD CAPACITY	2040	1940	1890	1890	1840
12 VOLT CONNECTION	4 WAY FLAT	4 WAY FLAT	4 WAY FLAT	4 WAY FLAT	4 WAY FLAT
RAMP SIZE/STYLE	48" MESH	48" MESH	48" MESH	48" MESH	48" MESH
FLOOR	2 X 8 TREATED	2 X 8 TREATED	2 X 8 TREATED	2 X 8 TREATED	2 X 8 TREATED
TIEDOWNS	Stakepockets	Stakepockets	Stakepockets	Stakepockets	Stakepockets
FRONT JACK	YES	YES	YES	YES	YES
DOT LIGHTING	YES	YES	YES	YES	YES
SAFETY CHAINS	1/4" GR. 70	1/4" GR. 70	1/4" GR. 70	1/4" GR. 70	1/4" GR. 70
FENDERS					
STANDARD	STEEL	STEEL	STEEL	STEEL	STEEL
OPTIONAL*	ALUMINUM*	ALUMINUM*	ALUMINUM*	ALUMINUM*	ALUMINUM*

Specifications subject to change without notice