



Standard Gooseneck Trailers



Features:

Various Lengths
L.E.D. Tail Lights
Treated Wood Floor
Underbody Toolbox

Radial Tires
Steps
Adjustable Downpipe
Document Holder

Popular Options:

8' Self Store Ramps
Twin Jacks
2 Speed Jacks

Some models may show optional equipment

See back of sheet for specifications

Standard Gooseneck

MODEL	F20GT-14	F24GT-14	F26GT-14	F26GT-24
BED LENGTH	20'	24'	26'	26'
BED WIDTH	102"	102"	102"	102"
RAMP STYLE	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
FLOOR HEIGHT	36"	36"	36"	36"
AXLE				
QUANTITY	TANDEM	TANDEM	TANDEM	TANDEM
CAPACITY	7,000 LB.	7,000 LB.	7,000 LB.	12,000 LB.
TYPE	TORSION	TORSION	TORSION	LEAF SPRING
BEARING LUBE	EZ-LUBE	EZ-LUBE	EZ-LUBE	OIL BATH
BRAKES	ELECTRIC	ELECTRIC.	ELECTRIC	ELECTRIC
BREAKAWAY KIT	STANDARD	STANDARD	STANDARD	STANDARD
TIRE SIZE	ST235R16	ST235R16	ST235R16	ST235R16
TIRE LOAD RANGE	E	E	E	E
WHEEL BOLT PATTERN	8 – 6 1/2	8 – 6 1/2	8 – 6 1/2	8 – 6 1/2
HITCH BALL SIZE	2 5/16"	2 5/16"	2 5/16"	2 5/16"
HITCH HEIGHT	ADJUSTABLE	ADJUSTABLE	ADJUSTABLE	ADJUSTABLE
CURB WEIGHT	4000	4400	5000	7,000
GVWR	14,000	14,000	14,000	25,400
PAYLOAD CAPACITY	10,000	9,600	9,000	17,000
12 VOLT CONNECTION	7 WAY RV	7 WAY RV	7 WAY RV	7 WAY RV
FRAME MATERIAL	I-BEAM	I-BEAM	I-BEAM	I-BEAM
SIZE OF FRAME	12 X 16	12 X 16	12 X 16	12 X19
CROSSMEMBERS	3" CHANNEL	3" CHANNEL	3" CHANNEL	3" CHANNEL
Crossmember spacing	16" O.C.	16" O.C.	16" O.C.	12" O.C.
FLOOR	2 X 8 TREATED	2 X 8 TREATED	2 X 8 TREATED	2 X 8 TREATED
TIE-DOWNS	POCKETS & RUBRAIL	POCKETS & RUBRAIL	POCKETS & RUBRAIL	POCKETS & RUBRAIL
JACK	12,000 LB. DROPLEG	12,000 LB. DROPLEG	12,000 LB. DROPLEG	Twin 12,000 LB. DROPLEG
DOT LIGHTING	YES	YES	YES	YES
SAFETY CHAINS	3/8" GR. 70	3/8" GR. 70	3/8" GR. 70	3/8" GR. 70

Specifications subject to change without notice