



Whale Tail Gooseneck Trailers



Features:

12" I-Beam Frame
Adjustable Downpipe
Treated Wood Floor

Two Full Width Foldover Ramps
Document Holder
Underbody Toolbox



Some models may show optional equipment

See back of sheet for specifications

Whale Tail Goosenecks

MODEL	830WT-20	832WT-20	832WT-24	836WT-24	840WT-24
BED LENGTH	30'	32'	32'	36'	40'
BED WIDTH	102"	102"	102"	102"	102"
RAMP STYLE	TWO FOLDOVER	TWO FOLDOVER	TWO FOLDOVER	TWO FOLDOVER	TWO FOLDOVER
BEAVERTAIL	PERMANENT	PERMANENT	PERMANENT	PERMANENT	PERMANENT
FLOOR HEIGHT	36"	36"	36"	36"	36"
AXLE QUANTITY CAPACITY TYPE	TANDEM 10,000 LB. DUAL	TANDEM 10,000 LB. DUAL	TANDEM 12,000 DUAL	TANDEM 12,000 DUAL	TANDEM 12,000 DUAL
BEARING LUBE	OIL BATH	OIL BATH	OIL BATH	OIL BATH	OIL BATH
BRAKES	ELECTRIC	ELECTRIC.	ELECTRIC	ELECTRIC	ELECTRIC
BREAKAWAY KIT	YES	YES	YES	YES	YES
TIRE SIZE	ST235R16	ST235R16	ST235R16	ST235R16	ST235R16
TIRE LOAD RANGE	E	E	E	E	E
WHEEL BOLT PATTERN	8 – 6 1/2	8 – 6 1/2	8 – 6 1/2	8 – 6 1/2	8 – 6 1/2
HITCH BALL SIZE	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
HITCH HEIGHT	ADJUSTABLE	ADJUSTABLE	ADJUSTABLE	ADJUSTABLE	ADJUSTABLE
CURB WEIGHT	6500	6600	6800	7400	7800
GVWR	23,400	23,400	25,400	25,400	25,400
PAYLOAD CAPACITY	16,900	16,800	18,600	18,000	17,600
12 VOLT CONNECTION	7 WAY RV	7 WAY RV	7 WAY RV	7 WAY RV	7 WAY RV
FRAME MATERIAL	I-BEAM	I-BEAM	I-BEAM	I-BEAM	I-BEAM
SIZE OF FRAME	12 X19	12 X 19	12 X 19	12 X 19	12 X 19
CROSSMEMBERS	3" CHANNEL	3" CHANNEL	3" CHANNEL	3" CHANNEL	3" CHANNEL
Crossmember spacing	12" O.C.	12" O.C.	12" O.C.	12" O.C.	12" O.C.
FLOOR	2 X 8 TREATED	2 X 8 TREATED	2 X 8 TREATED	2 X8 TREATED	2 X 8 TREATED
TIE-DOWNS	POCKETS & RUBRAIL	POCKETS & RUBRAIL	POCKETS & RUBRAIL	POCKETS & RUBRAIL	POCKETS & RUBRAIL
JACK	TWIN DROPLEG	TWIN DROPLEG	TWIN DROPLEG	TWIN DROPLEG	TWIN DROPLEG
DOT LIGHTING	YES	YES	YES	YES	YES
TOOLBOX	13" X 13" X 39"	13" X 13" X 39"	13" X 13" X 39"	13" X 13" X 39"	13" X 13" X 39"
SAFETY CHAINS	3/8" GR. 70	3/8" GR. 70	3/8" GR. 70	3/8" GR. 70	3/8" GR. 70

Specifications subject to change without notice