

Industrial Duty Trailers

MODEL	20IN-14BT	22IN-14BT	24IN-14BT
BED LENGTH	20'	22'	24'
BED WIDTH	82"	82"	82"
FLOOR HEIGHT	25"	25"	25"
Floor to top of Fender Height	11"	11"	11"
AXLE			
QUANTITY	TANDEM	TANDEM	TANDEM
CAPACITY	7,000 lb.	7,000 lb.	7,000 lb.
TYPE	Torsion	Torsion	Torsion
BEARING LUBE	EZ-LUBE	EZ-LUBE	EZ-LUBE
BRAKES	Electric	Electric	Electric
BREAKAWAY KIT	STANDARD	STANDARD	STANDARD
TIRE SIZE	ST235R16	ST235R16	ST235R16
TIRE LOAD RANGE	E	E	E
WHEEL BOLT PATTERN	8 – 6 1/2	8 – 6 1/2	8 – 6 1/2
HITCH BALL SIZE	2 5/16" Adjustable Height	2 5/16" Adjustable Height	2 5/16" Adjustable Height
HITCH HEIGHT	19"	19"	19"
HITCH WEIGHT	260 LBS.	280 LBS.	300 LBS.
CURB WEIGHT	2600 LBS.	2800 LBS.	3000 LBS.
GVWR	14,000 LB.	14,000 LB.	14,000 LB.
PAYLOAD CAPACITY	11,400 LBS.	11,200 LBS.	11,000 LBS.
12 VOLT CONNECTION	7 WAY RV	7 WAY RV	7 WAY RV
FRAME MATERIAL	8" I-BEAM	8" I-BEAM	8" I-BEAM
CROSSMEMBERS	3" CHANNEL	3" CHANNEL	3" CHANNEL
Crossmember spacing	16" O.C.	16" O.C.	16" O.C.
RAMP SIZE/STYLE			
STANDARD	5' SELF STORE	5' SELF STORE	5' SELF STORE
OPTIONAL*	5' FOLD-UP	5' FOLD-UP	5' FOLD-UP
FLOOR	2 X 8 TREATED	2 X 8 TREATED	2 X 8 TREATED
TIE-DOWNS	STAKE POCKETS	STAKE POCKETS	STAKE POCKETS
JACK	12,000 LB. DROPLEG	12,000 LB. DROPLEG	12,000 LB. DROPLEG
DOT LIGHTING	YES	YES	YES
SAFETY CHAINS	5/16" GR. 70	5/16" GR. 70	5/16" GR. 70
FENDERS	10 X 73 12 GAUGE	10 X 73 12 GAUGE	10 X 73 12 GAUGE

Specifications subject to change without notice